Sky Factory ēScape™ 2.0 Digital Cinema

DC-eScape-4123 Specifications

Ultra High Definition (UHD) video screen imbedded in a wall mounted frame Screen surface recessed in window frame evokes a sense of depth and enhances the architectural realism of dynamic landscapes

Video Content

8 hours standard* of long form, real time, continuous 4K UHD (3840 x 2160) and Full HD (1920 x 1080) videos played on a 4K Ultra HD monitor in 3840 x 2160 Videos range from 45 to 110 minutes with no loops, jump-cuts, or accelerated motion Plug in module allows for changing or adding additional content with no data network needed, providing reliable and secure use Video captured with 4K RED One or RED Epic camera * Longer play times available

Monitor:

49" (1245mm) Professional LED Edgelit LCD Monitor Resolution: Ultra High Definition 3840 x 2160

Mounting Pan with Integrated Video Playback Equipment:

Mounting Pan

16 gauge steel, powder coated silver

Provides one location for all playback equipment

Protects eScape monitor and video playback equipment, facilitates wiring,

and provides ventilation for proper cooling

Rough opening: call the Sky Factory for specific requirements

Requires wire access from top during rough-in for power and signal cable to controller

Junction box with 1/2" (22mm) trade size knock-outs; where conduit is specified, flexible will be required

Video-audio playback equipment

Simple plug-in module for additional content

Wall Mounted Controller

Wired via Cat 6 cable Simple illuminated push button operation Fits in single gang outlet box Low voltage mounting bracket provided Keypad bezel available in white, almond or black Standard Decora style faceplate available in white, almond, black or stainless steel Other faceplate options available from Leviton

Cabling:

One plenum rated Cat 6 cable Monitor location to wall mounted controller Ends terminated with RJ45 connectors 35'(15.3m) standard, alternate lengths available if specified

Wood or brushed anodized clear or black aluminum (style and material selected by client) Sizes vary with style and material selection 30 1/2" (775mm) to 33" (838mm) wide 49 1/16" (1246mm) to 52 1/16" (1333mm) high 7/16" (11mm) to 2" (51mm) deep from wall surface

Electrical Requirements:

Input: 100-240V AC, 50-60Hz Total Power Consumption: 217 Watts

Circuit Recommendations: a separate circuit is advisable Power Surge Protection: recommended, but not provided Operating Temperature: 32F ~ 104F (OC ~ 40C) Operating Humidity: 10% ~ 80 % non-condensing

Warranty:

2 year Sky Factory, Inc. limited warranty on entire system

ēScape™

Recessed Wall Mount Ultra High Definition (UHD) Digital Cinema Virtual Window



Viewable Area:

approx. 41" x 23" (1041mm x 584mm) depending on trim selection

Fixture Weight:

 $38.4 \, \text{lbs} + 10.1 \, \text{to} \, 28.9 \, \text{lbs} \, \text{depending on trim choice}$ (17.5 kg + 4.6 to 13.1 kg depending on trim choice)

Notice: This product is NOT compatible with MRI and high energy particle imaging environments, such as Linac.

This document specifies product only. For rough opening and installation specifications, call the Sky Factory.

